

**RAS-3M26U2AVG-E - Performances data Tri-split size 26**

Operating status	Combination			Unit capacity (kW)			Cooling capacity (kW)			Power input (W)			Operating current (A)		EER	Seasonal efficiencies*		
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min.	Nom.	Max.	Min.	Nom.	Max.	Nom.	Pdesign		SEER	SEER	Class
1 room	05	-	-	1.50	-	-	1.3	1.5	2.0	-	-	-	-	-	-	-	-	-
	07	-	-	2.00	-	-	1.4	2.0	2.7	-	-	-	-	-	-	-	-	-
	10	-	-	2.70	-	-	1.4	2.7	3.4	-	-	-	-	-	-	-	-	-
	13	-	-	3.70	-	-	1.4	3.7	4.3	-	-	-	-	-	-	-	-	-
	16	-	-	4.50	-	-	1.4	4.5	5.5	-	-	-	-	-	-	-	-	-
	18	-	-	5.00	-	-	1.4	5.0	5.7	-	-	-	-	-	-	-	-	-
	22	-	-	6.00	-	-	2.4	6.0	6.7	-	-	-	-	-	-	-	-	-
	24	-	-	7.10	-	-	2.4	7.1	7.7	-	-	-	-	-	-	-	-	-
2 rooms	05	05	-	1.50	1.50	-	2.5	3.0	4.5	640	690	1900	3.16	4.32	3.0	-	-	
	07	05	-	2.00	1.50	-	2.5	3.5	5.0	640	830	1950	3.80	4.22	3.5	-	-	
	10	05	-	2.50	1.50	-	2.5	4.2	6.3	640	1030	2000	4.71	4.08	4.2	-	-	
	13	05	-	3.50	1.50	-	2.5	5.2	6.5	640	1340	2300	6.13	3.89	5.2	-	-	
	16	05	-	4.60	1.50	-	2.5	6.0	7.1	640	1600	2500	7.32	3.74	6.0	-	-	
	18	05	-	5.00	1.50	-	2.5	6.5	7.1	640	1780	2500	8.15	3.66	6.5	-	-	
	22	05	-	5.92	1.48	-	2.5	7.4	8.4	640	2150	2690	9.84	3.50	7.4	-	-	
	24	05	-	6.11	1.29	-	2.5	7.4	8.4	640	1980	2760	9.06	3.74	7.4	-	-	
	07	07	-	2.00	2.00	-	2.5	4.0	6.3	640	950	1900	4.35	4.21	4.0	-	-	
	10	07	-	2.70	2.00	-	2.5	4.7	6.3	640	1200	1900	5.49	3.92	4.7	-	-	
	13	07	-	3.70	2.00	-	2.6	5.7	6.5	660	1600	2220	7.32	3.56	5.7	-	-	
	16	07	-	4.08	1.82	-	2.7	5.9	6.6	660	1700	2220	7.78	3.47	5.9	-	-	
	18	07	-	4.50	1.80	-	2.9	6.3	6.9	670	2000	2400	9.15	3.15	6.3	-	-	
	22	07	-	4.73	1.58	-	2.9	6.3	7.1	670	2000	2400	9.15	3.15	6.3	-	-	
	24	07	-	5.31	1.49	-	3.0	6.8	7.4	690	2200	2450	10.07	3.09	6.8	-	-	
	10	10	-	2.70	2.70	-	2.5	5.4	6.3	640	1500	1900	6.86	3.60	5.4	-	-	
	13	10	-	3.41	2.49	-	2.7	5.9	6.6	660	1700	2220	7.78	3.47	5.9	-	-	
	16	10	-	3.94	2.36	-	2.9	6.3	6.9	670	2000	2400	9.15	3.15	6.3	-	-	
	18	10	-	4.09	2.21	-	2.9	6.3	7.1	670	2000	2400	9.15	3.15	6.3	-	-	
	22	10	-	4.69	2.11	-	3.0	6.8	7.4	690	2200	2450	10.07	3.09	6.8	-	-	
	24	10	-	5.22	1.98	-	3.2	7.2	7.8	700	2300	2500	10.53	3.13	7.2	-	-	

05	05	05	1.50	1.50	1.50	3.8	4.5	6.3	950	1150	1710	5.26	4.02	4.5	6.65	A++
07	05	05	2.00	1.50	1.50	3.8	5.0	6.3	950	1300	1710	5.95	3.93	5.0	6.49	A++
10	05	05	2.70	1.50	1.50	3.8	5.7	6.3	950	1250	1710	5.72	3.80	5.7	6.28	A++
13	05	05	3.70	1.50	1.50	3.8	6.7	7.4	950	1500	1780	6.86	3.62	6.7	5.99	A+
16	05	05	4.44	1.48	1.48	3.8	7.4	8.8	950	1750	2520	8.01	3.50	7.4	5.79	A+
18	05	05	4.63	1.39	1.39	3.8	7.4	8.8	950	1780	2520	8.15	3.50	7.4	5.79	A+
22	05	05	4.93	1.23	1.23	3.8	7.4	8.8	950	2150	2780	9.84	3.50	7.4	5.79	A+
24	05	05	5.20	1.10	1.10	3.8	7.4	8.8	950	1980	2770	9.06	3.74	7.4	6.18	A++
07	07	05	2.00	2.00	1.50	3.8	5.5	6.3	950	1250	1710	5.72	3.84	5.5	6.34	A++
10	07	05	2.70	2.00	1.50	3.8	6.2	6.9	950	1350	1710	6.18	3.71	6.2	6.13	A++
13	07	05	3.70	2.00	1.50	3.8	7.2	8.4	950	1650	1810	7.55	3.53	7.2	5.84	A+
16	07	05	4.16	1.85	1.39	3.8	7.4	8.8	950	1780	2520	8.15	3.50	7.4	5.79	A+
18	07	05	4.35	1.74	1.31	3.8	7.4	8.8	950	1960	2520	8.97	3.50	7.4	5.79	A+
22	07	05	4.67	1.56	1.17	3.8	7.4	8.8	950	1970	2770	9.02	3.76	7.4	6.21	A++
24	07	05	4.96	1.40	1.05	3.8	7.4	8.8	950	1980	2780	9.06	3.74	7.4	6.18	A++
10	10	05	2.70	2.70	1.50	3.8	6.9	7.4	950	1600	1780	7.32	3.59	6.9	5.93	A+
13	10	05	3.47	2.53	1.41	3.8	7.4	8.8	950	1740	2520	7.96	3.50	7.4	5.79	A+
16	10	05	3.83	2.30	1.28	3.8	7.4	8.8	950	2040	2520	9.34	3.50	7.4	5.79	A+
18	10	05	4.02	2.17	1.21	3.8	7.4	8.8	950	1970	2760	9.02	3.76	7.4	6.21	A++
22	10	05	4.35	1.96	1.09	3.8	7.4	8.8	950	1980	2770	9.06	3.74	7.4	6.18	A++
24	10	05	4.65	1.77	0.98	3.8	7.4	8.8	950	1980	2780	9.06	3.74	7.4	6.18	A++
13	13	05	3.08	3.08	1.25	3.8	7.4	8.8	950	2110	2690	9.66	3.50	7.4	5.79	A+
16	13	05	3.43	2.82	1.14	3.8	7.4	8.8	950	1970	2770	9.02	3.76	7.4	6.21	A++
18	13	05	3.63	2.68	1.09	3.8	7.4	8.8	950	1980	2770	9.06	3.74	7.4	6.18	A++
22	13	05	3.96	2.44	0.99	3.8	7.4	8.8	950	1980	2780	9.06	3.74	7.4	6.18	A++
24	13	05	4.27	2.23	0.90	3.8	7.4	8.8	950	1990	2790	9.11	3.72	7.4	6.15	A++
16	16	05	3.17	3.17	1.06	3.8	7.4	8.8	950	1980	2770	9.06	3.74	7.4	6.18	A++
18	16	05	3.36	3.03	1.01	3.8	7.4	8.8	950	1980	2780	9.06	3.74	7.4	6.18	A++
22	16	05	3.70	2.78	0.93	3.8	7.4	8.8	950	1990	2790	9.11	3.72	7.4	6.15	A++
24	16	05	4.06	2.58	0.86	3.8	7.5	9.0	950	2000	2800	9.15	3.75	7.5	6.20	A++
18	18	05	3.22	3.22	0.97	3.8	7.4	8.8	950	1990	2780	9.11	3.72	7.4	6.15	A++
22	18	05	3.60	3.00	0.90	3.8	7.5	9.0	950	1990	2790	9.11	3.77	7.5	6.23	A++
24	18	05	3.92	2.76	0.83	3.8	7.5	9.0	950	2000	2800	9.15	3.75	7.5	6.20	A++
22	22	05	3.33	3.33	0.83	3.8	7.5	9.0	950	2000	2800	9.15	3.75	7.5	6.20	A++
07	07	07	2.00	2.00	2.00	3.8	6.0	8.4	950	1400	2720	6.41	4.28	6.0	5.71	A+
10	07	07	2.70	2.00	2.00	3.8	6.7	8.4	950	1660	2720	7.60	4.03	6.7	5.86	A+
13	07	07	3.56	1.92	1.92	3.9	7.4	8.6	960	1975	2750	9.04	3.74	7.4	5.92	A+
16	07	07	3.92	1.74	1.74	3.9	7.4	8.6	960	1975	2750	9.04	3.74	7.4	5.93	A+

18	07	07	4.11	1.64	1.64	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.89	A+
22	07	07	4.44	1.48	1.48	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.17	A++
24	07	07	4.73	1.33	1.33	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.16	A++
10	10	07	2.70	2.70	2.00	3.8	7.4	8.4	950	1850	2720	8.47	4	7.4	5.96	A+
13	10	07	3.26	2.38	1.76	3.9	7.4	8.6	960	1975	2750	9.04	3.74	7.4	5.92	A+
16	10	07	3.62	2.17	1.61	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.92	A+
18	10	07	3.81	2.06	1.53	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.89	A+
22	10	07	4.15	1.87	1.38	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.17	A++
24	10	07	4.45	1.69	1.25	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.16	A++
13	13	07	2.91	2.91	1.57	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.91	A+
16	13	07	3.26	2.68	1.45	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.92	A+
18	13	07	3.46	2.56	1.38	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.89	A+

**RAS-3M26U2AVG-E** - Performances data Tri-split size 26

Operating status	Combination			Unit capacity (kW)			Cooling capacity (kW)			Power input (W)			Operating current (A)	EER	Seasonal efficiencies*			
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min.	Nom.	Max.	Min.	Nom.	Max.	Nom.		Pdesign	SEER	Class	
Cooling, 230 V	3 rooms	22	13	07	3.79	2.34	1.26	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.17	A++
		24	13	07	4.10	2.14	1.16	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.16	A++
		16	16	07	3.03	3.03	1.35	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.06	A+
		18	16	07	3.22	2.90	1.29	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.15	A++
		22	16	07	3.60	2.70	1.20	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		24	16	07	3.92	2.48	1.10	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		10	10	10	2.47	2.47	2.47	3.9	7.4	8.6	960	1975	2750	9.04	3.74	7.4	5.92	A+
		13	10	10	3.01	2.20	2.20	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.91	A+
		16	10	10	3.36	2.02	2.02	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.92	A+
		18	10	10	3.56	1.92	1.92	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.89	A+
		22	10	10	3.89	1.75	1.75	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.17	A++
		24	10	10	4.20	1.60	1.60	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.16	A++
		13	13	10	2.71	2.71	1.98	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.91	A+
		16	13	10	3.06	2.51	1.83	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.92	A+
		18	13	10	3.25	2.40	1.75	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.02	A+
		22	13	10	3.63	2.24	1.63	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.17	A++
		24	13	10	3.94	2.06	1.50	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.17	A++
		16	16	10	2.85	2.85	1.71	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.19	A++
		18	16	10	3.03	2.73	1.64	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.15	A++
		22	16	10	3.41	2.56	1.53	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		24	16	10	3.72	2.36	1.42	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		13	13	13	2.47	2.47	2.47	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	5.91	A+
		16	13	13	2.80	2.30	2.30	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.05	A+
		18	13	13	2.98	2.21	2.21	4.0	7.4	8.8	970	1975	2770	9.04	3.74	7.4	6.02	A+
		22	13	13	3.36	2.07	2.07	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.17	A++
		24	13	13	3.67	1.91	1.91	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.17	A++
		16	16	13	2.66	2.66	2.19	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.19	A++
		18	16	13	2.84	2.56	2.10	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.16	A++
		22	16	13	3.17	2.38	1.95	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		24	16	13	3.48	2.21	1.81	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.18	A++
		16	16	16	2.50	2.50	2.50	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.20	A++
		18	16	16	2.68	2.41	2.41	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.16	A++
		22	16	16	3.00	2.25	2.25	4.1	7.5	9.0	980	2000	2800	9.15	3.75	7.5	6.19	A++

Operating status	Combination			Unit capacity (kW)			Heating capacity (kW)			Power input (W)			Operating current (A)	COP	Seasonal efficiencies*			
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min.	Nom.	Max.	Min.	Nom.	Max.			Nom.	Pdesign	SEER	Class
Heating, 230 V	2 rooms	05	-	-	2.00	-	-	0.8	2.0	2.7	-	-	-	-	-	-	-	
		07	-	-	2.70	-	-	0.8	2.7	3.6	-	-	-	-	-	-	-	
		10	-	-	4.00	-	-	0.8	4.0	5.0	-	-	-	-	-	-	-	
		13	-	-	5.00	-	-	0.8	5.0	5.5	-	-	-	-	-	-	-	
		16	-	-	5.50	-	-	0.8	5.5	6.7	-	-	-	-	-	-	-	
		18	-	-	6.00	-	-	0.8	6.0	6.3	-	-	-	-	-	-	-	
		22	-	-	7.00	-	-	1.8	7.0	7.5	-	-	-	-	-	-	-	
		24	-	-	8.10	-	-	1.8	8.1	8.8	-	-	-	-	-	-	-	
		05	05	-	2.00	2.00	-	2.0	4.0	6.4	320	850	1400	3.89	4.94	3.6	-	-
		07	05	-	2.70	2.00	-	2.0	4.7	6.9	320	1050	1540	4.81	4.83	3.8	-	-
		10	05	-	4.00	2.00	-	2.0	6.0	7.4	320	1350	1680	6.18	4.63	4.0	-	-
		13	05	-	5.00	2.00	-	2.0	7.0	8.9	320	1560	2120	7.14	4.48	4.5	-	-
		16	05	-	5.50	2.00	-	2.0	7.5	9.5	320	1700	2300	7.78	4.40	4.8	-	-
		18	05	-	5.70	1.90	-	2.0	7.6	9.8	320	1850	2400	8.47	4.39	4.8	-	-
		22	05	-	5.99	1.71	-	2.0	7.7	11.2	320	1980	2760	9.06	4.37	4.8	-	-
		24	05	-	6.34	1.56	-	2.0	7.9	11.2	320	1980	2770	9.06	3.99	5.0	-	-
		07	07	-	2.70	2.70	-	1.5	5.4	7.4	320	1400	2900	6.86	3.86	4.0	-	-
		10	07	-	4.00	2.70	-	1.5	6.7	8.9	320	1950	3050	9.52	3.44	4.5	-	-
		13	07	-	4.81	2.59	-	1.5	7.4	9.5	320	2300	3200	10.53	3.22	4.8	-	-
		16	07	-	5.10	2.50	-	1.5	7.6	9.5	320	2300	3200	10.53	3.30	4.8	-	-
		18	07	-	5.45	2.45	-	1.5	7.9	9.5	320	2450	3200	11.21	3.22	5.0	-	-
		22	07	-	5.70	2.20	-	1.5	7.9	9.8	320	2450	3200	11.21	3.22	5.0	-	-
		24	07	-	6.23	2.08	-	1.5	8.3	10.1	320	2500	3250	11.44	3.32	5.0	-	-
		10	10	-	3.60	3.60	-	1.5	7.2	9.5	320	2200	3200	10.07	3.27	4.8	-	-
		13	10	-	4.22	3.38	-	1.5	7.6	9.5	320	2300	3200	10.53	3.30	4.8	-	-
		16	10	-	4.57	3.33	-	1.5	7.9	9.5	320	2450	3200	11.21	3.22	5.0	-	-
		18	10	-	4.74	3.16	-	1.5	7.9	9.8	320	2450	3200	11.21	3.22	5.0	-	-
		22	10	-	5.28	3.02	-	1.5	8.3	10.1	320	2500	3250	11.44	3.32	5.0	-	-
		24	10	-	5.76	2.84	-	1.5	8.6	10.4	320	2550	3250	11.67	3.37	5.0	-	-
		13	13	-	3.95	3.95	-	1.5	7.9	9.8	320	2450	3200	11.21	3.22	5.0	-	-
		16	13	-	4.35	3.95	-	1.5	8.3	10.1	320	2500	3250	11.44	3.32	5.0	-	-
		18	13	-	4.53	3.77	-	1.5	8.3	10.1	320	2500	3250	11.44	3.32	5.0	-	-
		22	13	-	5.02	3.58	-	1.5	8.6	10.4	320	2550	3250	11.67	3.37	5.0	-	-
		24	13	-	5.32	3.28	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-
		16	16	-	4.30	4.30	-	1.5	8.6	10.4	320	2550	3250	11.67	3.37	5.0	-	-
		18	16	-	4.49	4.11	-	1.5	8.6	10.4	320	2550	3250	11.67	3.37	5.0	-	-
22	16	-	4.82	3.78	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-		
24	16	-	5.12	3.48	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-		
18	18	-	4.30	4.30	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-		
22	18	-	4.63	3.97	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-		
24	18	-	4.94	3.66	-	1.5	8.6	10.8	320	2550	3250	11.67	3.37	5.0	-	-		

3 rooms	05	05	05	2.00	2.00	2.0	2.0	6.0	9.5	380	1220	1400	5.58	4.92	4.0	5.34	A+++
---------	----	----	----	------	------	-----	-----	-----	-----	-----	------	------	------	------	-----	------	------

**RAS-3M26U2AVG-E - Performances data Tri-split size 26**

Operating status	Combination			Unit capacity (kW)			Heating capacity (kW)			Power input (W)			Operating current (A)		COP	Seasonal efficiencies*		
	Unit A	Unit B	Unit C	Unit A	Unit B	Unit C	Min.	Nom.	Max.	Min.	Nom.	Max.	Nom.	Pdesign		SEER	Class	
Heating, 230 V	3 rooms	18	13	05	4.11	3.42	1.37	2.0	8.9	11.2	380	2180	2780	9.98	4.08	5.2	4.43	A+
		22	13	05	4.45	3.18	1.27	2.0	8.9	11.2	380	2180	2790	9.98	4.08	5.2	4.43	A+
		24	13	05	4.77	2.95	1.18	2.0	8.9	11.2	380	2180	2800	9.98	4.08	5.2	4.43	A+
		16	16	05	3.77	3.77	1.37	2.0	8.9	11.2	380	2180	2780	9.98	4.08	5.2	4.43	A+
		18	16	05	3.96	3.63	1.32	2.0	8.9	11.2	380	2180	2790	9.98	4.08	5.2	4.43	A+
		22	16	05	4.30	3.38	1.23	2.0	8.9	11.2	380	2180	2790	9.98	4.08	5.2	4.43	A+
		24	16	05	4.67	3.17	1.15	2.0	9.0	11.2	380	2200	2800	10.07	4.09	5.2	4.44	A+
		18	18	05	3.81	3.81	1.27	2.0	8.9	11.2	380	2180	2790	9.98	4.08	5.2	4.43	A+
		22	18	05	4.20	3.60	1.20	2.0	9.0	11.2	380	2200	2800	10.07	4.09	5.2	4.44	A+
		24	18	05	4.53	3.35	1.12	2.0	9.0	11.2	380	2200	2800	10.07	4.09	5.2	4.44	A+
		22	22	05	3.94	3.94	1.13	2.0	9.0	11.2	380	2200	2800	10.07	4.09	5.2	4.44	A+
		07	07	07	2.70	2.70	2.70	2.0	8.1	10.8	380	1800	2750	8.24	4.50	5.2	4.43	A+
		10	07	07	3.53	2.38	2.38	2.0	8.3	10.8	380	1900	2750	8.70	4.37	5.2	4.43	A+
		13	07	07	4.28	2.31	2.31	2.0	8.9	10.8	380	2175	2750	9.95	4.09	5.2	4.43	A+
		16	07	07	4.49	2.20	2.20	2.0	8.9	10.8	380	2175	2750	9.95	4.09	5.2	4.44	A+
		18	07	07	4.68	2.11	2.11	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		22	07	07	5.02	1.94	1.94	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		24	07	07	5.34	1.78	1.78	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		10	10	07	3.18	3.18	2.14	2.0	8.5	10.8	380	2000	2750	9.15	4.25	5.2	4.43	A+
		13	10	07	3.80	3.04	2.05	2.0	8.9	10.8	380	2175	2750	9.95	4.09	5.2	4.43	A+
		16	10	07	4.01	2.92	1.97	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+
		18	10	07	4.20	2.80	1.89	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		22	10	07	4.55	2.60	1.75	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		24	10	07	4.87	2.41	1.62	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		13	13	07	3.50	3.50	1.89	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		16	13	07	3.71	3.37	1.82	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+
		18	13	07	3.90	3.25	1.75	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		22	13	07	4.24	3.03	1.63	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		24	13	07	4.56	2.82	1.52	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		16	16	07	3.57	3.57	1.75	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+
		18	16	07	3.76	3.45	1.69	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		22	16	07	4.14	3.26	1.60	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+
		24	16	07	4.47	3.04	1.49	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+
		10	10	10	2.97	2.97	2.97	2.0	8.9	10.8	380	2175	2750	9.95	4.09	5.2	4.43	A+
		13	10	10	3.42	2.74	2.74	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		16	10	10	3.63	2.64	2.64	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+
		18	10	10	3.81	2.54	2.54	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
		22	10	10	4.15	2.37	2.37	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		24	10	10	4.48	2.21	2.21	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.29	A+
		13	13	10	3.18	3.18	2.54	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+
16	13	10	3.38	3.07	2.46	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+		
18	13	10	3.56	2.97	2.37	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+		
22	13	10	3.94	2.81	2.25	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.29	A+		
24	13	10	4.26	2.63	2.11	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.29	A+		
16	16	10	3.26	3.26	2.37	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+		
18	16	10	3.45	3.16	2.30	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+		
22	16	10	3.82	3.00	2.18	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+		
24	16	10	4.14	2.81	2.05	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+		
13	13	13	2.97	2.97	2.97	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+		
16	13	13	3.16	2.87	2.87	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.44	A+		
18	13	13	3.34	2.78	2.78	2.0	8.9	11.0	380	2175	2830	9.95	4.09	5.2	4.43	A+		
22	13	13	3.71	2.65	2.65	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.29	A+		
24	13	13	4.03	2.49	2.49	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.29	A+		
16	16	13	3.09	3.09	2.81	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.44	A+		
18	16	13	3.27	3.00	2.73	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.43	A+		
22	16	13	3.60	2.83	2.57	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+		
24	16	13	3.92	2.66	2.42	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+		
16	16	16	3.00	3.00	3.00	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.45	A+		
18	16	16	3.18	2.91	2.91	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.44	A+		
22	16	16	3.50	2.75	2.75	2.0	9.0	11.2	380	2200	2900	10.07	4.09	5.2	4.30	A+		



**Look for this number in the model number of you indoor unit**